

CARBON STEEL HYDRAULIC FITTINGS J.I.C.- SAE J514

Standard - Jumpsize - Special













Gauge Line Connection Port

Air-Way simplifies ordering of Gauge Line Connection Port fittings in all shapes & sizes. Use the photograph to select the port location, add the symbol as a suffix to the part number and show the combined size and position.

Example: 6801-8-8-NWO-2P2.

6801-8-8-NWO2
90° Adjustable Elbow
Size
Position



Order Information

Sizes of the fittings are indicated by the dash numbers as relating to sixteenth's of an inch measured from the Outside Diameter of the tube size used. For example; 1/2" O.D. (8/16) is noted as - 8. Male or Female pipe sizes are similar in that 1/2" pipe thread is also (8/16) or - 8.

Our standard items can be ordered by using the appropriate chart and dash numbers. For example: 2501-8-12 is a 1/2" tube with 3/4-16 straight thread on one end, and 3/4" pipe thread on the other end.

Adjustable and O-Ring fittings may be purchased in various stages of assembly. For example: 6801-8-8-NWO would be assembled complete with "N" Nut, "W" Washer and "O" O-Ring. 6801-8-8-NW would be assembled with "N" Nut and "W" Washer only.

Many items are available in either a brazed or forged style construction. If a forged style is preferred, simply add a "G" prefix to the item number or the word "Forging" after the number.

Special items and configurations are available to order using customer specifications. Pricing and availability of these items can be furnished on request.

The Air-Way Advantage

Since 1950, Air-Way Global Manufacturing Company has been the leading manufacturer of hydraulic fittings.

Not only is Air-Way an ISO 9001 and ISO 14001 certified manufacturer, but also a certified supplier to several of the largest and most recognized Original Equipment Manufacturers in the world.

Air-Way is the largest independent hydraulic fitting manufacturer in the United States. The combination of our manufacturing expertise, along with our outstanding technical and customer service support has proven to represent an excellent value for our customers.

We have also made available a program called Air-Way Direct™. This program allows us to ship the same day we receive your order. Only with Air-Way Direct™ can you benefit from both the technical expertise of a manufacturer along with immediate delivery of product.

Special packaging, shipping and service programs have helped Air-Way establish a reputation as being the most versatile and customer friendly manufacturer in the hydraulic fitting industry.

Air-Way Global Manufacturing
- The World Source For Hydraulic Fittings -



AIR-WAY GLOBAL MANUFACTURING COMPANY | 586 N. MAIN STREET | OLIVET, MI 49076 P 800-253-1036 | P 269-749-2161 | F 269-749-2046 | E sales@AIR-WAY.com | W AIR-WAY.com

Adapter Union

Refer to "Adapter Unions & Pipe Fittings" Chart below for sizes

NOTE:

Also available in FLARE-O® and Stainless Steel Styles.













(1) Male Pipe (2) Female Pipe Swivel









(1, 2 & 3) Female Pipe Swivel





Pipe Fittings

Refer to "Adapter Unions & Pipe Fittings" Chart for sizes







(1 & 2) Male Pipe



(1 & 2) Male Pipe

























(3) Female Pipe



















Adapter Unions & Pipe Fittings

DASH NUMBER	2	4	6	8	12	16	20	24	32
Pipe Th'd NPSM – NPTF	1/8	1/4	3/8	1/2	3/4	1	1-1/4	1-1/2	2
Decimal	.125	.250	.375	.500	.750	1.000	1.250	1.500	2.000
M.M. Equiv.	3.175	6.350	9.525	12.700	19.050	25.400	31.750	38.100	50.800

Adjustable & O-Ring Fittings

Refer to "Tube Fittings, JIC-SAE" Chart for sizes

NOTE:

Also available in FLARE-O® and Stainless Steel Styles.



6400-O - Str. (1) Male Tube (2) Male O-Ring



6400-L-O - Str. (1) Male Tube (2) Male O-Ring-Long



6401-O - Str. (1) Male O-Ring (2) Male Pipe



6402-O - Str. (1) Male O-Ring (2) 37° Female Swivel



6403-O - Str. (1&2) Male O-Ring



6404 - Str. (1) Female O-Ring (2) Male Pipe



6405-O Str. (1) Male O-Ring (2) Female Pipe



6407-NWO - Str. (1) Male O-Ring (2) Adjustable O-Ring



6408-0 Plug (1) Male O-Ring - Ext. Hex



6409-0 - Plug (1) Male O-Ring - Int. Hex



6410-0 - Str. (1) Male O-Ring (2) Female O-Ring



6801-NWO - 90° (1) Male Tube (2) Adjustable O-Ring



6801-L-NWO - 90° (1) Male Tube (2) Adjustable O-Ring-Long



6801-LL-NWO 90° (1) Male Tube (2) Adjustable O-Ring Ex-Long



6801-LLL-NWO - 90° (1) Male Tube (2) Adjustable O-Ring Ex-Ex-Long



6802-NWO - 45° (1) Male Tube (2) Adjustable O-Ring



6803-NWO - Tee (1 & 2) Male Tube (3) Adjustable O-Ring



6804-NWO - Tee (1 & 3) Male Tube (2) Adjustable O-Ring



6805-NWO - 90° (1) Adjustable O-Ring (2) Female Pipe



6806-NWO - 90° (1) Adjustable O-Ring (2) Male Pipe



6807-NWO - 90° (1 & 2) Adjustable O-Ring



6808-NWO - 45° (1 & 2) Adjustable O-Ring



6809-NWO 90° (1) Adjustable O-Ring (2) 37° Female Swivel



6810-NWO - 45° (1) Adjustable O-Ring (2) 37° Female Swivel



6900-O - Str. (1) Male O-Ring (2) Female Pipe Swivel



6901-NWO - 90° (1) Adjustable O-Ring (2) Female Pipe Swivel



6902-NWO - 45° (1) Adjustable O-Ring (2) Female Pipe Swivel





4603-NWO - 45° (1) Beaded (2) Adjustable O-Ring



4604-O - Str. (1) Beaded (2) Male O-Ring



4605-NWO - Tee (1 & 3) Beaded (2) Male O-Ring



Tube Fittings, JIC-SAE

DASH NUMBER	2	3	4	5	6	8	10	12	14	16	18	20	24	32
Tube O.D.	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	7/8	1	1-1/8	1-1/4	1-1/2	2
Decimal	.125	.188	.250	.313	.375	.500	.625	.750	.875	1.000	1.125	1.250	1.500	2.000
M.M. Equiv.	3.175	4.763	6.350	7.938	9.525	12.700	15.875	19.050	22.225	25.400	28.575	31.750	38.100	50.800
Straight Thread	5/16-24	3/8-24	7/16-20	1/2-20	9/16-18	3/4-16	7/8-14	1-1/16-12	1-3/16-12	1-5/16-12	1-1/2-12	1-5/8-12	1-7/8-12	2-1/2-12
Decimal-threads/inch	.313	.375	.438	.500	.563	.750	.875	1.063	1.188	1.313	1.500	1.625	1.875	2.500
	-24	-24	-20	-20	-18	-16	-14	-12	-12	-12	-12	-12	-12	-12
M.M. Equiv.	7.938	9.525	11.113	12.700	14.288	19.050	22.225	26.988	30.163	33.338	38.100	41.275	47.625	63.500
	-24	-24	-20	-20	-18	-16	-14	-12	-12	-12	-12	-12	-12	-12
Pipe Thread Standard	1/8	1/8	1/8	1/8	1/4	3/8	1/2	3/4	3/4	1	1	1-1/4	1-1/2	2
Decimal	.125	.125	.125	.125	.250	3.75	.500	.750	.750	1.000	1.000	1.250	1.500	2.0000
M.M. Equiv.	3.175	3.175	3.175	3.175	6.350	9.525	12.700	19.050	19.050	25.400	25.400	31.750	38.100	50.800

NOTE: Also available in FLARE-O® and Stainless Steel Styles.



6501 - 90° 1) Male Pine (2) 37° Female Swivel







(2) 37° Female Swivel

6505 - Str. (1) Male Pipe (2) 37° Female Swivel





6507 - 45°

(1) Female Pipe (2) 37° Female Swivel















NOTE:

Items shown with "G" in the top portion of the box are also available in a Forged style. To order the Forged style, simply add a G prefix to the item number. For example, G6801-6-6-NWO.

Applicable items are also shown with an SAE number in the top portion of the box. In example, (070220).

Braze Fittings for Tubing Refer to "Tube Fittings, JIC-SAE" Chart for sizes



403 - Str. Unplated (1) Bore (2) Male Tube



403-L - Str. Unplated (1) Bore (2) Bulkhead



404 - Str. Unplated (1) Bore (2) Male Pipe



405 - Str. Unplated (1) Bore (2) Female Pipe



500 - 90° Unplated (1) Bore (2) Male Tube



501 - 90° Unplated (1) Bore (2) Male Pipe



600 - Tee Unplated (1 & 2) Bore (3) Male Tube



602 - Tee Unplated (1 & 2) Bore (3) Female Pipe



701 - Elbow Unplated (1) Bore (2 & 3) Male Tube



702 - Tee Unplated (1) Bore (2 & 3) Male Tube



800 - Str. Unplated (1) Bore (2) Female Pipe Swivel



801 - 90° Unplated (1) Bore (2) Female Pipe Swivel



900 - Str. Unplated



901 - 90° Unplated (1) Bore (2) 37°Female Swivel

Flanges Refer to "Tube Fittings, JIC-SAE" Chart for sizes



1700 - Str. (2) O-Ring Flange



1701 - 90° 1) Male Tube (2) O-Ring Flange



1703 - 45° (1) Male Tube (2) O-Ring Flange



1704 - 90° (1) Male Tube (2) O-Ring Flange



3300 - Unplated (1 & 2) 3000 PSI Flange



3300-H - Unplated (1 & 2) 6000 PSI Flange









Tube Fittings

4404 - Str.

(1) Beaded (2) Male Pipe **4501 -** 90°

(2) Male Pipe

4503 - 45°

(2) Male Pipe

4504 - Tee

(1, 2, & 3) Beaded

4505 - Tee

(1 & 3) Beaded

(2) Male Pipe

4506 - Tee

(1 & 2) Beaded (3) Male Pipe **6500 -** 90°

(1) Male Tube

(2) 37° Female Swivel

Refer to "Tube Fittings, JIC-SAE" Chart for sizes

NOTE: Also available in FLARE-O® and Stainless Steel Styles.

